


## Double Clevis Link (TCSH356)

- Grade 70, only for lashing and pulling. Never to be used for lifting.
- Forged alloy steel- Quenched and Tempered.
- Suitable for G70 transport chain.

| Size | W.L.L (t) | B.L (t) | Dimension (mm) | | | | | N.W. (kg/pc) |
|---|---|---|---|---|---|---|---|---|
| | | | A | B | M | N | L | |
| 1/4" | 1.18 | 4.72 | 32 | 13.2 | 19.5 | 37.5 | 72.5 | 0.17 |
| 5/16" | 2.45 | 9.8 | 39.5 | 14.7 | 25.9 | 52.5 | 90.7 | 0.37 |
| 7/16" | 3.17 | 12.68 | 44.2 | 18 | 29.3 | 57.5 | 104 | 0.57 |
| 1/2" | 4.17 | 16.68 | 51 | 21.2 | 32.3 | 63.5 | 116 | 0.71 |
| 5/8" | 7.94 | 31.76 | 56.8 | 19.8 | 41.4 | 81 | 144 | 1.30 |






## G80 Container Hook (TCSH472)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

| Size | W.L.L (t) | B.L (t) | Dimension (mm) | | | | | | N.W. (kg/pc) |
|---|---|---|---|---|---|---|---|---|---|
| | | | A | B | E | H | M | L | |
| 13-8 | 5 | 20 | 16 | 54.5 | 58.4 | 37 | 127 | 186 | 1.5 |






## Concrete Precast Element Lifting (TCSH547)

- Component A: casted super alloy.
- Component B: forged alloy steel.
- 100% magnaflux crack detection.
- Surface finish: electric galvanized, or powder coated.
- Ultimated load is 5 times of working load limit.

| W.L.L (t) | B.L (t) | Dimension (mm) | | | | | | | N.W. (kg/pc) |
|---|---|---|---|---|---|---|---|---|---|
| | | A | B | C | D | H | E | L | |
| 2.5 | 12.5 | 95 | 70 | 58.8 | 27 | 58 | 35 | 264 | 1.58 |
| 5 | 25 | 117 | 85 | 66.2 | 37 | 82 | 45 | 333 | 3.58 |
| 10 | 50 | 148 | 110 | 84.6 | 50 | 110 | 56 | 424 | 9 |









## G80 Container Hook (TCSH633)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Straight Type
直型




| Size | W.L.L (t) | B.L (t) | Dimension (mm) | | | | | | | | | N.W. (kg/pc) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | A | M | H | h | E | R | D | d | L | |
| 633-S | 12.5 | 50 | 46 | 75 | 166 | 25 | 48 | 60 | 70 | 25 | 265 | 4 |

Left Type
左45°型




| Size | W.L.L (t) | B.L (t) | Dimension (mm) | | | | | | | | | N.W. (kg/pc) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | A | M | H | h | E | R | D | d | L | |
| 633-L | 12.5 | 50 | 46 | 75 | 166 | 25 | 48 | 60 | 70 | 25 | 265 | 4 |

Right Type
右45°型




| Size | W.L.L (t) | B.L (t) | Dimension (mm) | | | | | | | | | N.W. (kg/pc) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | A | M | H | h | E | R | D | d | L | |
| 633-R | 12.5 | 50 | 46 | 75 | 166 | 25 | 48 | 60 | 70 | 25 | 265 | 4 |






## G80 New Eye Screw (TCSH902)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

| Size | W.L.L (t) | B.L (t) | Dimension (mm) | | | | | |
|---|---|---|---|---|---|---|---|---|
| | | | A | B | C | Φ | F | L |
| M8 | 0.3 | 1.2 | 47 | 25 | 8 | 25.5 | 9 | 47 |
| M10 | 0.4 | 1.6 | 47 | 25 | 8 | 25.5 | 12 | 47 |
| M12 | 0.75 | 3 | 56 | 33 | 10 | 30 | 14 | 55 |
| M16 | 1.5 | 6 | 65.2 | 36 | 14 | 35 | 19.5 | 66 |
| M20 | 2.3 | 9.2 | 75 | 45 | 17 | 40.5 | 26 | 76.5 |
| M24 | 3.2 | 12.8 | 88 | 53 | 20 | 48 | 42.5 | 93 |
| M30 | 4.5 | 18 | 112 | 62 | 24 | 60 | 40 | 116 |
| M36 | 7 | 28 | 130 | 78 | 29 | 72 | 53.5 | 135 |